Accessories

		Order No.	Price/€
O	H-UV changeover valve 3-way changeover valve for switching 2-storage tank systems or solar stratification. ¾", 230 V.	1002690	122.00
	Solar station in thermal box Two-line pump group DN25 for collector area from 4 to approx.40 m². Consisting of flow limiter, safety valve 6 bar, pressure gauge 10 bar, 2 thermometers, 2 shut-off valves, 2 non-return valves, 2 connections for filling and purging, block insulation, wall bracket, fixing screws and compression ring screws. With MAG connection set and de-aerator cylinder. 2-point solar controller incl. storage tank sensor and collector sensor.	1001063	930.00
	Solar liquid H-PE 10 For flat collectors. Corrosion and frost protection in the solar circuit with high thermal transmittance. Non-toxic. Biologically degradable to DIN 4757. Canister 10 kg.	1001014	82.95
	H-AG expansion vessel Membrane expansion vessel filled with nitrogen. Prepressure set to 2.5 bar. Connection G ¾". Operating temperature –10 to +110 °C. With EC type certificate.		
	H-AG expansion vessel 18 l	1001012	102.00
	H-AG expansion vessel 25 l	1000998	111.00
	H-AG expansion vessel 40 l	1001013	155.50
	Solar Duo flexible pipe, DN 16 Stainless steel corrugated pipes in HT insulation. Flow and return insulator in 2 parallel chambers. Temperature resistant up to 150 °C. UV resistant. For laying outdoors without additional protection measures. Incl. ¾" ÜM. Can be shortened on site.		
	Solar-Duo flexible pipe, DN 16 roll, 10 m	1001002	419.00
	Solar-Duo flexible pipe, DN 16 roll, 15 m	1001003	640.00
	Solar-Duo flexible pipe, DN 16 roll, 20 m	1001004	839.00
	Solar Duo flexible pipe, DN 20 (as above, however DN 20)		
The state of the s	Solar-Duo flexible pipe, DN 20 roll, 10 m	1001005	493.00
	Solar-Duo flexible pipe, DN 20 roll, 15 m	1001006	732.00
1	Collector flow sensor PT1000/6	1001758	34.82
	SPF sensor for storage tank, length 3m	1000994	33.10

^{*} Further types of installation such as flat roof, façade or in-roof installation on request. Prices are given as additional charge per collector.

Adapted solar controller available on request